

Product Code: CMA022

## **Technical Specification**



Description: 20A Double Pole Plate Switch With Optional Flex Outlet







## **General Information**

Plate Dimensions (mm)  $86 \text{ (W)} \times 86 \text{ (H)} \times 9.5 \text{ (D)}$ 

Plate Fixing Centres - Horizontal (mm) 60.3

Style Rounded Profile Colour Polar White

Materials Front Plate & Rocker Switch: Urea Rear Housing: Urea

Terminals: Brass Terminal Screws: Steel & Yellow Passivated
Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Flex Outlet Dimension (mm) Ø10

Earth Strap: Mild Steel

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20 Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.8

Terminal Capacity - Solid (mm²) 3 × 2.5

Double Pole Switch Yes

Twin Earth Terminals Yes

Flex Outlet Available Yes

Anti Microbial Certified

Flex Outlet Location Bottom of Plate

Minimum Back Box Depth (mm) 25

Ingress Protection IP20
Operational Temperature (°C) -5 to +40

Warranty (Years) 25

Standards BS EN 60669-1

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

E: sales@scolmore.com | W: scolmore.com









