

Product Code: CMA044

## **Technical Specification**



Description: 20A Double Pole 'Water Heater' Switch With Optional Flex Outlet







## **General Information**

Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Colour Polar White

Materials Front Plate & Rocker Switch: Urea Rear Housing: Urea

> Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Operating Voltage (AC) Frequency (Hz) 50 250

Resistive Load Rating (A) Termination Type Screw

Anti Microbial Certified

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.8

Terminal Capacity - Solid (mm²) 3 x 2.5 Double Pole Switch Yes Twin Earth Terminals Yes

Product Marking Water Heater

Flex Outlet Available Yes

Flex Outlet Location Bottom of Plate Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) Ingress Protection Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-1

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com









