

Technical Specification



Product Code: CMA148PL Luckinslive 397119921 Description: 2 Gang Unfurnished Dimmer Plate & Knobs (1600W Max) - 4 Apertures



General Information

Plate Dimensions (mm)	146 (W) × 86 (H) × 9.5 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Rounded Profile	
Colour	Polar White	
Materials	Front Plate & Control Button: Urea	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Earth Strap: Mild Steel
Anti Microbial Certified	Yes	
Termination Type	Screw	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	25	
Standards BS 5733		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module MD9010: 1-10V Analogue Rotary Dimmer Module	Compatible Dimmer Modules MD9014: 100W Dual Mode LED Dimmer Module
--	--

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com









