

Technical Specification

Product Code: CMA162

Description: 2 Gang 2 Way 100W Dimmer Switch

Luckinslive 425262504







General Information Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D) Plate Fixing Centres - Horizontal (mm) 603 Rounded Profile Style Materials Front Plate: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated PCB: Mixed Components Anti Microbial Certified Yes Operating Voltage (AC) 250 Frequency (Hz) 50 Load Rating (W) 5 - 100 Load Rating Comments Suitable For LED Termination Type Screw Terminal Size (mm) Ø3.5 Terminal Torque Value (Nm) 0.25 Terminal Capacity - Solid (mm²) 2 X 1.5 2 Way Switch Yes Switch Control Type Press - ON/OFF, Rotate - Dim Dimmer Technology Type Trailing Edge Minimum Brightness Programming Available Minimum Back Box Depth (mm) 25 Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years) 25 Warranty - Electronics (Years) 2 BS EN 60669-1, BS EN 60669-2-1, BS EN 55015, BS EN 61000-3-2 Standards For cleaning / polishing of products, use only a soft, dry, clean cloth. Additional We recommend the use of branded LED lamps with all Mode® trailing edge dimmers. The use of inferior, non-Information branded lamps may require the nominal rating of the dimmer to be reduced. For further information please contact Click® Technical support team. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae. MDg014: 100W Dual Mode LED Dimmer Module Compatible MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module **Dimmer Modules** MD9010: 1-10V Analogue Rotary Dimmer Module

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Specification is subject to change without notice. Errors & Omissions excluded.



Page 1 of 1 (02-01-2024)







