

Product Code: CMA432

## **Technical Specification**

Luckinslive 392590011



Description: 2 Gang MiniGrid® Unfurnished Plate - 3 Apertures



## **General Information**

Plate Dimensions (mm) 146 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

MiniGrid Plate (Gang)

MiniGrid Single Width Module Quantity

MiniGrid Double Width Module Quantity

Style Rounded Profile Colour Polar White

Materials Front Plate: Urea

Anti Microbial Certified Yes Modular Rocker Switches

Minimum Back Box Depth (mm) Dependent On Modules Fitted

Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years)

**Standards** BS 5733

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99,9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Interchangeable with modules in the MiniGrid Range.













Specification is subject to change without notice. Errors & Omissions excluded.