

Technical Specification



Product Code: CMA612 Luckinslive 404183468

Description: 2 Tier MiniGrid® Unfurnished Plate & Yokes - 12 Apertures



General Information

Plate Dimensions (mm) $146 \text{ (W)} \times 153 \text{ (H)} \times 9.5 \text{ (D)}$

 $\begin{tabular}{ll} MiniGrid Plate (Gang) & 12 \\ MiniGrid Single Width Module Quantity & 12 (2 <math display="inline">\times$ 6) \\ \end{tabular}

MiniGrid Double Width Module Quantity 6

Style Mode
Colour Polar White

Materials Front Plate: Urea
Terminal Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Anti Microbial Certified Yes

Termination Type Screw
Modular Rocker Switches Yes

Yoke Earth Terminal Supplied One Earth On Each Yoke

Yoke Required No

Minimum Back Box Depth (mm) 47

Ingress Protection IP20
Operational Temperature (°C) -5 to +40
Warranty (Years) 25

Standards BS 5733

Earthing Yoke: Mild Steel Terminals: Brass

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Interchangeable with modules in the MiniGrid Range













