

Technical Specification



Product Code: CMA630BL

Luckinslive 425139666

Description: 13A 1 Gang Socket Outlet With Twin Earth Terminals - Blue (Medical Equipment Only)





General Information

| Plate Dimensions (mm) | 86 (W) x 86 (H) x 9.5 (D) | | |
|--|---------------------------|--|----|
| Plate Fixing Centres - Horizontal (mm) | 60.3 | | |
| Style | Rounded Profile | | |
| Colour | Blue | | |
| Materials | Front Plate: Urea | Rear Housing: Urea | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Earth Strap: Mild Steel | | |
| Anti Microbial Certified | Yes | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 13 | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) | 2 |
| Terminal Capacity - Solid (mm²) | 3 x 2.5 or 2 x 4 | | |
| Switched | No | | |
| Twin Earth Terminals | Yes | | |
| Minimum Back Box Depth (mm) | 25 | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 25 | | |
| Standards BS 1363-2 | | | |

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









