

Product Code: CMA660

Luckinslive 407531004

Description: 20A Double Pole 1 Gang Plate Key Lockable Switch



General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Rounded Profile		
Colour	Polar White		
Materials	Front Plate: Urea Terminals: Brass GridPro Module: GM2018PW	Earth Plate & Yoke: Mild Steel Terminal Screws: Steel & Yellow Passivated	
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	20		
Termination Type	Screw	Terminal Torque Value (Nm)	1.2
Terminal Size (mm)	Ø5		
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Switched	Yes (via Key)		
Modular Rocker Switches	Yes		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Product Marking	On & Off		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Two keys provided (Spare keys available: SP660)

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

