

Technical Specification



Luckinslive 402031059



Description: 13A 2 Gang Switched Socket Outlet With Single 2.1A USB Outlet





General Information

Plate Dimensions (mm)	146 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Rounded Profile		
Colour	Polar White		
Materials	Front Plate & Rocker Switch: Urea	Rear Housing: Nylor)
	Terminals: Brass	Terminal Screws: Ste	eel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Br	ass Internal Busbars: For	rmed Pressed Brass
	PCB: Mixed Components	Earth Strap: Mild Ste	el
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
USB Output Type	USB Type 'A'		
USB Number Of Outputs	1	USB Charging Total Load (A)	2.1
USB Charging Voltage (V DC)	5	USB Standby Current (mA)	2
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Single Pole Switched	Yes		
Twin Earth Terminals	Yes		
Product Marking	USB 5V 2.1A		
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25 V	Narranty - Electronics (Years)	2
Standards BS 1363-2: 2016 +A1: 2018, BS EN IEC 62368-1, BS EN 62680-1-1			

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com

Specification is subject to change without notice. Errors & Omissions excluded.



Page 1 of 1 (02-01-2024)







