

Product Code: CMA811

Technical Specification

Luckinslive 401155211



Description: 10AX 1 Gang 2 Way Wide Rocker Switch



Frequency (Hz) 50

Terminal Torque Value (Nm) 0.5

General Information

Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Colour Polar White

Materials Front Plate & Rocker Switch: Urea Rear Housing: Nylon

> Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Anti Microbial Certified Operating Voltage (AC) 250

Inductive Load Rating (AX)

Load Rating Comments Suitable for Fluorescent or Inductive Loads

Terminal Size (mm) Ø3.5

Termination Type Screw

Terminal Capacity - Solid (mm²) 2 x 1.5

Modular Rocker Switches 2 Way Switch

Minimum Back Box Depth (mm)

IP20 Ingress Protection

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Specification is subject to change without notice. Errors & Omissions excluded.









