



Product Code: ES001

Luckinslive 389119049

Description: 13A 1 Gang Trailing Socket Outlet With Neon



General Information

Dimensions (mm)	96 (W) x 62 (D) x 27 (H)		
Materials	Housing: Polycarbonate	Neon Lens: Polycarbonate	
	Internal Busbars: Brass	Terminals: Brass	
	Terminal Screws: Steel and Yellow Passivated		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm²)	1.5		
Number Of Socket Outlets	1		
Switched	No		
Neon Indicator	Yes	Indicator Colour	Red
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation.
 Always refer to the circuit diagram supplied with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC

