

Product Code: ES008

Luckinslive 389119078

Description: 13A 3 Gang Trailing Socket Outlet With Neon



**General Information**

Dimensions (mm)	200 (W) x 62 (D) x 27 (H)		
Materials	Housing: Polycarbonate	Neon Lens: Polycarbonate	
	Internal Busbars: Brass	Terminals: Brass	
	Terminal Screws: Steel and Yellow Passivated		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm²)	1.5		
Number Of Socket Outlets	3		
Switched	No		
Neon Indicator	Yes	Indicator Colour	Red
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

**Standards** BS 1363-2

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation.  
 Always refer to the circuit diagram supplied with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

