

# SPECIFICATION SHEET

## LED AC DRIVERLESS FLOODLIGHTS



The LED AC Driverless Floodlights are available in 10W-300W and have a black finish.

### Applications:

- Commercial Sites
- Factories
- Leisure Centres



Image shown FLAC100B


### Specification

<b>LED:</b>	15-360pcs of SMD 2835
<b>Material:</b>	Aluminium
<b>Guarantee:</b>	2 Years
<b>Life Expectancy:</b>	>30,000 Hours
<b>Working Temperature:</b>	-20°C - 45°C
<b>Power Factor:</b>	>0.9
<b>Beam Angle:</b>	>120°
<b>CRI:</b>	>80 Ra

### Additional Information

- 75/80lm/W • Aluminium tray • Black finish
- Driverless technology • 3G 0.75mm<sup>2</sup> 1m Cable included
- Mounting bracket included • Internal white reflector
- HO5RN-F

### Dimensions



Code	Wattage	Colour Temperature	Lumen Output	Dimensions (L x W x D mm)
FLAC10B	10W	6000K	800lm	103 x 83 x 24
FLAC10B-31	10W	3100K	750lm	103 x 83 x 24
FLAC20B	20W	6000K	1600lm	160 x 122 x 25
FLAC20B-31	20W	3100K	1500lm	160 x 122 x 25
FLAC30B	30W	6000K	2400lm	160 x 122 x 25
FLAC30B-31	30W	3100K	2250lm	160 x 122 x 25
FLAC50B	50W	6000K	4000lm	206 x 160 x 31
FLAC50B-31	50W	3100K	3750lm	206 x 160 x 31
FLAC100B	100W	6000K	8000lm	270 x 210 x 31
FLAC150B	150W	6000K	12,000lm	379 x 279 x 43
FLAC200B	200W	6000K	16,000lm	379 x 279 x 43
FLAC300B	300W	6000K	24,000lm	445 x 335 x 45