

## iSpot Frameless



### Description

Ideal for residential applications such as houses, drives and patios. Designed with an aesthetically appealing super slim body.

### Features

- Air release valve to prevent condensation building up within fitting
- Frameless design improves IP rating
- Made from aluminum and toughened glass
- Driverless technology
- Angled bracket for easy installation
- Available in white or black
- Available with PIR option
- 3-year Guarantee

### Technical Specification

Voltage	220V-240V	
Frequency	50-60Hz	
Power Factor	≤0.9	
Colour Temperature	4000K Cool White	
Beam Angle	110°	
Construction	Aluminium Body & Toughened Glass	
IP Rating	IP65	
IK Rating	IK07	
Cable length	50cm	
Dimmable	No	
Light Source	Non-replaceable LED	
Lifespan	30,000hrs	
Luminous Flux	10W	900 lm
	20W	1800 lm
	30W	2700 lm
	50W	4500lm
Luminous Efficacy	90 lm/W	
Standards	BS EN 60598-1	

No user serviceable parts  
Contact your local authority for information concerning the correct disposal of your product

### Range

I2012	10W iSpot
I2022	20W iSpot
I2032	30W iSpot
I2042	50W iSpot
I2013	10W iSpot with PIR
I2023	20W iSpot with PIR
I2033	30W iSpot with PIR
I2043	50W iSpot with PIR

Available in White or Black, add W or B to item code

### PIR Specification

Detection Range	8m±2m
Detection Angle	120°
Time Delay	10sec ±5sec – 8min ±2min
Ambient Light	5-2000 lux
Installation Height	1.8m – 2.5m

### Weight & Dimensions

	Length	Width	Height	Weight
I2012	120mm	20mm	104mm	0.32Kg
I2022	120mm	20mm	163mm	0.36Kg
I2032	163mm	20mm	135mm	0.50Kg
I2042	163mm	20mm	191mm	0.55Kg
I2013	195mm	20mm	159mm	0.70Kg
I2023	195mm	20mm	215mm	0.77Kg
I2033	223mm	20mm	184mm	0.95Kg
I2043	235mm	20mm	239mm	1.01Kg

All dimensions are body and do not include the