



Product Code: CL023

Luckinslive 389086389

Description: 20A Double Pole Plate Switch With Neon & Optional Flex Outlet Insert



General Information

Dimensions (mm)	80 (W) x 80 (H) x 42 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Metal Clad		
Colour	Grey		
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Insert, Switch & Rear Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel	Frequency (Hz) 50
Operating Voltage (AC)	250		
Resistive Load Rating (A)	20		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.8
Terminal Capacity - Solid (mm²)	3 x 2.5		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Neon Indicator	Yes	Indicator Colour	Red
Flex Outlet Available	Yes		
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm)	Ø10
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	5 x Ø20		
Back Box Knockouts - Top (mm)	2 x Ø20	Back Box Knockouts - Sides (mm)	1 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20	Back Box Knockouts - Rear (mm)	None
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

