essentials[™]

Technical Specification

Product Code: CL035B Luckinslive 389086415

Description: 13A 1 Gang Double Pole Switched Socket Outlet





General Information

Dimensions (mm) 80 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Metal Clad Colour Grey

Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Rear Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Operating Voltage (AC) 250 Resistive Load Rating (A) 13

Termination Type Screw **Terminal Size (mm)** Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes

Supplied Back Box Depth (mm) 40
Back Box Knockouts - Total (mm) None
Back Box Earth Terminal Supplied Yes
Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-2

Insert & Rocker Switch: Urea

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel Frequency (Hz) 50

Terminal Torque Value (Nm) 2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Specification is subject to change without notice. Errors & Omissions excluded.