

Technical Specification

Luckinslive 389086428

Product Code: CL036

Description: 13A 2 Gang Double Pole Switched Socket Outlet





General Information

Dimensions (mm)	140 (W) x 80 (H) x 42 (D)			
Plate Fixing Centres - Horizontal (mm)	120.6			
Style	Metal Clad			
Colour	Grey			
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert & Rocker Swite	ch: Urea	
	Rear Housing: Urea	Terminals: Brass		
	Terminal Screws: Steel & Yellow Passivated	d Contacts: Silver "on-l	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Ste	Earth Strap: Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz)	50	
Resistive Load Rating (A)	13			
Termination Type	Screw			
Terminal Size (mm)	Ø5 Terminal Torque Value (Nm) 2		2	
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4			
Double Pole Switch	Yes			
Twin Earth Terminals	Yes			
Supplied Back Box Depth (mm)	40			
Back Box Knockouts - Total (mm)	7 × Ø20			
Back Box Knockouts - Top (mm)	3 x Ø20 Back Box k	Ø20 Back Box Knockouts - Sides (mm) 1		
Back Box Knockouts - Bottom (mm)	2 × Ø20 Back Box Knockouts - Rear (mm)		None	
Back Box Earth Terminal Supplied	Yes			
Ingress Protection	IP20			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	20			
Standards BS 1363-2				

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









