



Product Code: CL158

Luckinslive 389086570

Description: Single Isolated Coaxial Outlet



General Information

Dimensions (mm)	80 (W) x 80 (H) x 42 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Metal Clad		
Colour	Grey		
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert: Urea	
	Earth Plate: Mild Steel	Terminals: Brass	
Termination Type	Screw		
Isolated	Yes		
Isolated Comments	Enables 1 way signal, reducing signal interference		
Non-Isolated	No		
Shielded	No		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	5 x Ø20		
Back Box Knockouts - Top (mm)	2 x Ø20		Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20		Back Box Knockouts - Rear (mm) None
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.



Catalogue



Range



DoC



Installation

