## essentials™

Product Code: CL202

## **Technical Specification**

Luckinslive 389086606

Description: 45A 2 Gang (Vertical) Double Pole Plate Switch





## **General Information**

 $\textbf{Dimensions (mm)} \quad \text{80 (W)} \times \text{140 (H)} \times \text{52 (D)}$ 

Plate Fixing Centres - Vertical (mm) 120.6

Style Metal Clad

Colour Grey

Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Operating Voltage (AC) 250

Resistive Load Rating (A) 45

Termination Type Screw

Terminal Size (mm) Ø6

Terminal Capacity - Solid (mm<sup>2</sup>)  $1 \times 16$ 

Double Pole Switch Yes
Twin Earth Terminals Yes

Product Marking On & Off

Supplied Back Box Depth (mm) 50

Back Box Knockouts - Total (mm) 7 x Ø20

Back Box Knockouts - Top (mm)  $3 \times \emptyset 20$ Back Box Knockouts - Bottom (mm)  $2 \times \emptyset 20$ 

Back Box Earth Terminal Supplied

Ingress Protection IP2

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS EN 60669-1

Insert, Switch & Rear Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Frequency (Hz) 50

Terminal Torque Value (Nm) 2.

Back Box Knockouts - Sides (mm)  $1 \times \emptyset 20$ 

Back Box Knockouts - Rear (mm) None

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Specification is subject to change without notice. Errors & Omissions excluded.