## essentials<sup>™</sup>

Product Code: CL426

## **Technical Specification**

Luckinslive 389086693

Description: 2 Gang MiniGrid® Unfurnished Plate - 6 In-Line Apertures





## **General Information**

 $\textbf{Dimensions (mm)} \quad \text{140 (W)} \times \text{80 (H)} \times \text{42 (D)}$ 

Plate Fixing Centres - Horizontal (mm) 120.6

MiniGrid Plate (Gang) 2

MiniGrid Single Width Module Quantity 6 Inline

MiniGrid Double Width Module Quantity

Style Metal Clad

Colour Grey

Insert Colour White

Materials Front Plate & Mo

erials Front Plate & Mounting Box:

Electrophoretically Coated Steel
Terminals: Brass
Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Termination Type Screw

Supplied Back Box Depth (mm) 40

Back Box Knockouts - Total (mm)  $7 \times \emptyset 20$ 

Back Box Knockouts - Top (mm) 3 x Ø20

Back Box Knockouts - Bottom (mm) 2 x Ø20

Back Box Earth Terminal Supplied Yes
Operational Temperature (°C) -5 to

oerational Temperature (°C) -5 to +40 Warranty (Years) 20

,

T-1-1/-----

Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Knockouts - Rear (mm) None

Insert: Urea

Back Box Knockouts - Rear (mm

Standards BS 5733

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.













Specification is subject to change without notice. Errors & Omissions excluded.