essentials[™]

Technical Specification

Product Code: CL66oB Luckinslive 407530678

Description: 20A Double Pole 1 Gang Plate Key Lockable Switch







Insert: Urea

Terminal Torque Value (Nm)

Terminals: Brass

GridPro Module: GM2018PW

Frequency (Hz) 50

General Information

Dimensions (mm) 80 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Metal Clad

Colour Grey

Front Plate & Mounting Box: Materials

Electrophoretically Coated Steel Earth Plate & Yoke: Mild Steel

Terminal Screws: Steel & Yellow Passivated

Operating Voltage (AC) Resistive Load Rating (A) 20

> Termination Type Screw

Terminal Size (mm)

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Modular Rocker Switches Yes Double Pole Switch Yes

> Twin Earth Terminals Yes

> > Product Marking On & Off

Supplied Back Box Depth (mm)

Back Box Knockouts - Total (mm) None

Back Box Earth Terminal Supplied Yes

Ingress Protection

Operational Temperature (°C)

-5 to +40 Warranty (Years)

BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Two keys provided (Spare keys available: SP660)

Standards

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

IP20











