essentials[™]

Product Code: CL675B

Technical Specification

Luckinslive 407530898

Description: 13A 1 Gang Double Pole Key Lockable Switched Socket With Neon (Double Plate)







Insert: Urea

Terminal Torque Value (Nm)

Neon Lens: Polycarbonate

GridPro Module: GM2018PW

Frequency (Hz) 50

Indicator Colour Red

Terminal Screws: Steel & Yellow Passivated

General Information

Dimensions (mm) 140 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Metal Clad Colour Grey

Front Plate & Mounting Box: Materials

Electrophoretically Coated Steel

Earth Plate & Yoke: Mild Steel Terminals: Brass

Internal Busbars: Formed Pressed Brass

Operating Voltage (AC) Resistive Load Rating (A) 13

Screw Termination Type Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched Yes (via Key)

Modular Rocker Switches Yes Double Pole Switch Yes Twin Earth Terminals Yes

Neon Indicator

Product Marking On & Off

Supplied Back Box Depth (mm) Back Box Knockouts - Total (mm) Back Box Earth Terminal Supplied

> Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-1, BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Two keys provided (Spare keys available: SP660)

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.









Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com