

Technical Specification

Luckinslive 403357787

Product Code: CL835 Luckins Description: 13A 1 Gang Double Pole Switched Socket Outlet With Neon



General Information

	80 (W) x 80 (H) x 42 (D)			
Plate Fixing Centres - Horizontal (mm)	60.3			
Style	Metal Clad			
Colour	Grey			
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel		Insert: Urea	
	Rear Housing: Urea		Neon Lens: Polycarbonate	
	Terminals: Brass		Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass		Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel			
Operating Voltage (AC)	250		Frequency (Hz)	50
Resistive Load Rating (A)	13			
Termination Type	Screw			
Terminal Size (mm)	Ø5 Terminal Torque Value (Nm)		2	
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4			
Double Pole Switch	Yes			
Neon Indicator	Yes		Indicator Colour	Red
Supplied Back Box Depth (mm)	40			
Back Box Knockouts - Total (mm)	5 x Ø20			
Back Box Knockouts - Top (mm)	2 X Ø20 B	ack Box Kno	ckouts - Sides (mm)	1 × Ø20
Back Box Knockouts - Bottom (mm)	1 × Ø20	Back Box Knockouts - Rear (mm)		None
Back Box Earth Terminal Supplied	Yes			
Ingress Protection	IP20			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	20			
Standards BS 1363-2				

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Specification is subject to change without notice. Errors & Omissions excluded.



Page 1 of 1 (02-01-2024)







