essentials™

Product Code: CL840

Technical Specification



Insert: Urea

Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Description: 13A 2 Gang Double Pole Switched Socket Outlet With Outboard Rockers & Neons





General Information

Dimensions (mm) 140 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Metal Clad Colour Grey

Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Rear Housing: Urea

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13
Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3×2.5 or 2×4

Double Pole Switch Yes
Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Red

Supplied Back Box Depth (mm) 40 Back Box Knockouts - Total (mm) 7×020

Back Box Knockouts - Top (mm) 3 x Ø20

Back Box Knockouts - Sides (mm) 1 x Ø20

Back Box Knockouts - Bottom (mm) 2 x Ø20

Back Box Knockouts - Rear (mm) None

Back Box Earth Terminal Supplied Yes

 $\label{eq:local_problem} \begin{array}{ll} \mbox{Ingress Protection} & \mbox{IP20} \\ \mbox{Operational Temperature (°C)} & -5 \mbox{ to $^{+}\!40$} \end{array}$

Warranty (Years) 20

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal









