

**Product Code:** CT1016

**Description:** 230V 20A 16 Gang 4 Pole Lighting Management Box



### General Information

Dimensions (mm)	264 (W) x 269 (H) x 69 (D)	
Style	Metal Clad	
Insert Colour	Blue	
Materials	Front Plate & Back Box: Electrophoretically Coated Steel	Male & Female Connectors: Nylon (PA66)
	Terminals: Silver Plated Brass	Terminal Screws: Steel and Yellow Passivated
	Dust Covers: Polycarbonate	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

**Standards** BS 8488, BS EN 61535, BS 5733

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Pre-fabricating wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.

### Compatible Connectors

Input Connector: Input Connector: 3 Pole (CT203M) Connector Supplied  
Output Connectors: Compatible with 3 and 4 Pole Male Connectors