



A multi-purpose Emergency Conversion Pack for LED fittings from 5W to 75W. The plug and play connections ensure quick and easy connection to the fitting and driver.



## Specification

<b>Wattage:</b>	5-75W	
<b>Charging Current:</b>	250mA	
<b>Input Voltage:</b>	220-230V, 50Hz	
<b>Discharging Current:</b>	240mA-260mA	
<b>Initial Charge Time:</b>	24 Hours	
<b>Discharge Duration:</b>	3 Hours	
<b>Mounting:</b>	Fitted into ceiling with LED Panel light	
<b>Light Output:</b>	8-10% of mains lumens	
<b>IP Rating:</b>	IP20	
<b>Life Expectancy of Battery:</b>	4 years	
<b>Guarantee:</b>	2 year	
<b>Lamp Protection:</b>	Over charge and discharge protection	
<b>LED Indicator:</b>	Green indicator	
<b>Battery Spec.:</b>	19.2V 1500mAh Ni-Cd Battery	
<b>Material:</b>	Polycarbonate Housing & 4 wires (mains supply + LED driver & Charge indicator).	
<b>Class:</b>	Class II - must not be earthed.	
<b>Operating Temp.:</b>	-10° - 45°C.	
<b>Extra Info:</b>	Does not include LED Driver. The battery has a designed service life of 4 years, when the rated duration is not met the battery must be changed.	

MODEL	WATTAGE	SUITABLE PRODUCTS	BATTERY	DIMENSIONS (L x W x D mm)
EMLEDKIT-MP	5-75W	LED PANELS	NI-CD	219 x 104 x 44