

## **Technical Specification**

Product Code: PA311 Description: 13A Resilient Plug Top (3A Fused) Fast Grip Luckinslive 389120038





## **General Information**

Dimensions (mm) Colour	49.5 (W) × 21 (D) × 49.5 (H) Black	
Materials	Body: Nylon	Pins: Brass
	Internal Busbars: Formed Pressed Brass	Fuse: BS 1362 Approved
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	3	
Fuse Fitted Type	Plug Top Cartridge Fuse	
Termination Type	Screw	
Terminal Size (mm)	Ø3.1 Term	inal Torque Value (Nm) 0.4
Terminal Capacity - Solid (mm²)	1.5	
Product Marking	Fused	
Cable Entry Dimensions (mm)	Ø10.8	
Cable Restraint Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards BS 1363/A, BS 1362		
Additional Information		

For cleaning / polishing of products, use only a soft, dry, clean cloth. Always refer to the circuit diagram supplied with the relevant product.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarmworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com







