essentials[™]

Technical Specification

Product Code: PA380RD Luckinslive 389783844

Description: 13A Resilient Non-Standard Plug Top (13A Fused) Bar Grip





General Information

 $\textbf{Dimensions (mm)} \quad 49.5 \ (\text{W}) \times 21 \ (\text{D}) \times 49.5 \ (\text{H})$

Colour Rec

Materials Body: Nylon

Internal Busbars: Formed Pressed Brass Fuse: BS 1362 Approved 50 Frequency (Hz) 50

Pins: Brass

Operating Voltage (AC) 25 Resistive Load Rating (A) 13

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Ø3.1 Terminal Torque Value (Nm) 0.4

Terminal Capacity - Solid (mm²) 1.5

Product Marking Fused
Cable Entry Dimensions (mm) Ø10.8
Cable Restraint Supplied Yes

Ingress Protection IP20
Operational Temperature (°C) -5 to +40
Warranty (Years) 10

Standards BS 1363/A, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Always refer to the circuit diagram supplied with the relevant product.

The non-standard plugs are suitable for use only with the non-standard sockets, product codes CMA935 and CMA936.









Specification is subject to change without notice. Errors & Omissions excluded.