

Technical Specification

Luckinslive 389783815



Product Code: PA380WH Description: 13A Resilient Non-Standard Plug Top (13A Fused) Bar Grip



General Information

| Dimensions (mm) | 49.5 (W) x 21 (D) x 49.5 (H) | | |
|-------------------------------------|--|-------------------------|-----|
| Colour | White | | |
| Materials | Body: Nylon | Pins: Brass | |
| | Internal Busbars: Formed Pressed Brass | Fuse: BS 1362 Approv | red |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 13 | | |
| Fuse Fitted Type | Plug Top Cartridge Fuse | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø3.1 Ter | minal Torque Value (Nm) | 0.4 |
| Terminal Capacity - Solid (mm²) | 1.5 | | |
| Product Marking | Fused | | |
| Cable Entry Dimensions (mm) | Ø10.8 | | |
| Cable Restraint Supplied | Yes | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 10 | | |
| Standards BS 1363/A, BS 1362 | | | |

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Always refer to the circuit diagram supplied with the relevant product. The non-standard plugs are suitable for use only with the non-standard sockets, product codes CMA935 and CMA936.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com







