essentials™

Product Code: PRCo16

Technical Specification

Luckinslive 389120258

Description: T2 BC Loop-In Batten Lampholder With H.O. Skirt





General Information

Dimensions (mm) 86 (Dia) x 80

Colour Polar White

Materials Body & Skirt: Urea Rear Plate: Polycarbonate

> Internal Housing: Reinforced Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Springs: Spring Steel

Anti Microbial Certified Yes

Operating Voltage (AC) Frequency (Hz) 50

Resistive Load Rating (A) 2

Termination Type Screw

Terminal Size (mm) Ø3.5 Terminal Torque Value (Nm) 0.5

Terminal Capacity - Solid (mm²)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS EN 61184, BS 67

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Facility to loop in and out.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Specification is subject to change without notice. Errors & Omissions excluded.







