

Technical Specification

Product Code: PRC1033 Description: 9" T2 BC Ceiling Safety Pendant Set Luckinslive 434806993





General Information

Dimensions (mm)	96 (Dia) x 20		_
	86 (Dia) x 30		
Colour	Polar White		
Materials	Cover, Body & Skirt: Urea	Rear Plate: Polycarbonate	
	Terminals: Brass	Terminal Brass	
	Cable Type: 2G H05V2V2-F	Internal Housing: PPS	
	Springs: Spring Steel		
Operating Voltage (AC)	250	Frequency (Hz) 50	
Resistive Load Rating (A)	2		
Pre-wired Cable Specification	2G 0.75mm ² H05V2V2-F		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5	
Terminal Capacity - Solid (mm²)	2 × 1.5		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		
Standards BS EN 61184, BS	S EN IEC 60598-2-1, BS 67		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

The safety lampholder reduces the potential of electric shock during lamp installation and replacement.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com







