

## **Technical Specification**

Luckinslive 406879482



Product Code: PRC1440RD Description: 6A 4 Pole Fast Fit Plug-in Ceiling Rose



## **General Information**

| Dimensions (mm)                 | 70 (Dia) x 43 (D)               |                          |   |
|---------------------------------|---------------------------------|--------------------------|---|
| Colour                          | Red                             |                          |   |
| Terminal Housing Finish         | Red                             |                          |   |
| Insert Colour                   | Red                             |                          |   |
| Materials                       | Cover & Housings: Polycarbonate | Terminals& Screws: Brass |   |
|                                 | Contacts: Brass                 | Cable Grip: Nylon        |   |
|                                 | Cable Grip Screws: Plated Steel |                          |   |
| Operating Voltage (AC)          | 250                             | Frequency (Hz) 50/60     | C |
| Resistive Load Rating (A)       | 6                               |                          |   |
| Termination Type                | Screw                           |                          |   |
| Terminal Capacity - Solid (mm²) | 2 × 1.5                         |                          |   |
| Cable Restraint Supplied        | Yes                             |                          |   |
| Ingress Protection              | IP20                            |                          |   |
| Operational Temperature (°C)    | -5 to +50                       |                          |   |
| Warranty (Years)                | 10                              |                          |   |
| Standards BS 6972, BS 573       | 3                               |                          |   |

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Suitable for flush mounting or mounting on to BESA conduit connection boxes.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com







