

Product Code: PRW210

Luckinslive 389107556

Description: 45A Double Pole Pull Cord Switch With Mechanical 'On/Off' & Neon



General Information

Dimensions (mm)	86 (W) x 86 (H) x 43 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Round		
Colour	Polar White		
Materials	Cover & Pattress: Urea	Terminal Housing:	Urea
	Neon Lens: Polycarbonate	Terminals:	Brass
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars:	Formed Pressed Brass
	Earth Strap: Mild Steel	Pull Bell:	Urea
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	45		
Termination Type	Screw		
Terminal Size (mm)	Ø6	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm²)	1 x 6		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Neon Indicator	Yes	Indicator Colour	Orange
Mechanical Indicator	Yes		
Mechanical Indicator Type	On/Off Rotating Legend		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
 All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Catalogue



Range



DoC



Installation

