



Product Code: PRW211

Luckinslive 389107569

Description: 50A Double Pole Pull Cord Switch With Mechanical 'On/Off' & Neon



**General Information**

Dimensions (mm)	86 (W) x 86 (H) x 43 (D)			
Plate Fixing Centres - Horizontal (mm)	60.3			
Style	Round			
Colour	Polar White			
Materials	Front Plate:	Urea	Terminal Housing:	Urea
	Neon Lens:	Polycarbonate	Terminals:	Brass
	Terminal Screws:	Steel & Yellow Passivated	Internal Busbars:	Formed Pressed Brass
	Earth Strap:	Mild Steel	Pull Bell:	Urea
Anti Microbial Certified	Yes			
Operating Voltage (AC)	250	Frequency (Hz)	50	
Resistive Load Rating (A)	50			
Termination Type	Screw			
Twin Screw Terminals	Yes			
Terminal Size (mm)	Ø6.7	Terminal Torque Value (Nm)	2.5	
Terminal Capacity - Solid (mm²)	1 x 25			
Double Pole Switch	Yes			
Twin Earth Terminals	Yes			
Neon Indicator	Yes	Indicator Colour	Orange	
Mechanical Indicator	Yes			
Mechanical Indicator Type	On/Off Rotating Legend			
Minimum Back Box Depth (mm)	47			
Ingress Protection	IP20			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	25			

**Standards** BS EN 60669-1

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.  
 All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Catalogue



Range



DoC



Installation

