



List No. NM206/40

NH / NM / NMX

2 Way Consumer Unit Main Switch 40A



- Full metal enclosure
- Fixed busbar assembly
- 2W Main switch only

Product Specification Data		Revision Date: 15/10/2021
Mounting method	Surface mounted (plaster)	
Number of phases	1	
Protection	Miniature- / earth leakage circuit breaker	
Total number of groups	1	
Number of poles main switch	2	
Main switch rated current	40 A	
Over voltage protection	No	
Material housing	Steel	
Degree of protection (IP)	IP2XC	
Height	185 mm	
Width	130 mm	
Width in number of modular spacings	4	
Depth	104 mm	
Extension possible	No	
With transparent cover	No	
Lockable	No	
Product Standard/s	BS EN 61439-3	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Amperage	63 A	
Operating Voltage	230 V	
Type of Current	AC	
Consumer Unit Type	Main switch only	
Total final circuit modular ways	2	
Busbar type	Flexible	
Main switch rating	40 A	
Main switch final circuit modular ways	2	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Colour RAL

9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk